

[54] **INNER ROTARY CUTTERS FOR ELECTRIC SHAVERS AND MANUFACTURING PROCESSES FOR THE SAME**

[75] Inventor: Katsuya Asawa, Matsumoto, Japan

[73] Assignee: Izumi Seimitsu Kogyo Kabushiki Kaisha, Matsumoto, Japan

[21] Appl. No.: 841,641

[22] Filed: Mar. 20, 1986

[30] **Foreign Application Priority Data**

Mar. 29, 1985 [JP] Japan ..... 60-68176

Mar. 29, 1985 [JP] Japan ..... 60-68177

[51] Int. Cl.<sup>4</sup> ..... B26B 19/04

[52] U.S. Cl. .... 30/346.51; 30/43.6

[58] Field of Search ..... 30/346.51, 347, 43.6, 30/357, 350, 276, 263, 265

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

2,494,464 1/1950 Vivie et al. .... 30/347 X

4,262,416 4/1981 Van Hemmen et al. .... 30/346.51 X

4,630,370 12/1986 Hamada ..... 30/346.51

**FOREIGN PATENT DOCUMENTS**

631383 6/1936 Fed. Rep. of Germany ... 76/101 A

*Primary Examiner*—Douglas D. Watts

*Attorney, Agent, or Firm*—Jordan and Hamburg

[57] **ABSTRACT**

In an inner rotary cutter for an electric shaver formed by providing a rotary disk at its circumference with a plurality of blade sections at prescribed intervals, a cup-shaped base section is provided which is formed by extending a cylinder section from a circular section in the axial direction to a prescribed length, the base section on its circumference is provided, in one body, with vertically extended sections projecting in the axial direction, each vertically extended section at its tip is provided, in one body, with a horizontally extended section projecting approximately in the radial direction, and the front edge of the horizontally extended section in the direction of rotation is formed into a blade. A ceramic blade may be glued on the end face of the horizontally extended section.

**13 Claims, 22 Drawing Figures**

